

# elka

## 14mm ENGINEERED FLOORING



*Brushed & Oiled*



*Laquer.*

### Appearance General

#### Colour:

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

#### Grain:

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

#### Variations Within Species And Grades:

- Considerable variation among boards in colour and grain texture.

#### Specification:

- Grade: Rustic
- Oak origin: Ukraine
- 14mm x 189 x 1860mm, 3mm top veneer
- 2 starter boards in every pack
- Lacquer : 6 coats
- Oil: 2 coats
- Lacquer: Klumpp
- Oil brand: Treffert
- Core species: poplar
- Adhesive: Akzo Nobel
- FSC/PEFC certificate: No
- Janka score: 1360 'medium hardness'

### Workability

#### Installation:

- Professional recommended

#### Sanding:

- Good if the correct sanding sequence is followed

#### Installing methods allowed:

- Floating
- Gluing on to Wooden or Concrete Sub-Floor (full stick down)

#### Features and Advantages:

- Can be laid over under floor heating
- Can be sanded and re-finished
- Made 100% of natural wood
- Ensures excellent thermal and acoustic isolation
- Dimensional stability
- Floor can be laid in all residential areas (except those of high humidity)
- Elka complimentary accessory products available – underlay, adhesives, finishing profiles & maintenance products.

#### engineered flooring

- 1 finish
- 2 Hardwood wear layer
- 3 Engineered real wood core
- 4 Stabilising backing board.

