

ELKA

80mm NATURAL OAK FLOORING



Lacquered

Appearance General

DESCRIPTION	GRADE A	GRADE B
GRAIN	MIXED	MIXED
KNOTS	SOUND KNOTS ALLOWED EXCLUDE BLACK KNOT	10MM KNOTS ALLOW, BUT NO MORE THAN 5 IN ONE PIECE
PINE HOLE	LITTLE	ALLOW
CRACKS/SPLITS/	NOT ALLOWED	NOT ALLOWED
SAPWOOD	NOT ALLOWED	10% AREA IN 1 PIECE IS ALLOWED
COLOUR	LESS CONTRAST, SLIGHT COLOUR VARIATION	MORE CONTRAST ALLOWED BUT STILL UNIFORM
DISCOLORATIONS	NOT ALLOWED	SLIGHTLY ALLOWED

Specification:

- Grade: Rustic 'A/B'
- Oak origin: Germany, USA
- 18x130mm Random lengths 300 – 1200mm - average 630mm
- Lacquer : 8 coats
- Sheen: 40% Satin
- Lacquer brand: Treffert, German brand
- FSC/PEFC certificate: Yes at source
- Janka score: 1360 'medium hardness'

Workability

Installation:

- Professional recommended

Sanding:

- Good if the correct sanding sequence is followed

Installing methods allowed:

- *Nailing on to Wooden Sub-Floor*
- Gluing on to Wooden or Concrete Sub-Floor

Must never do:

- Must not be laid over under floor heating
- Must not be laid in a conservatory
- Must not be laid in bathrooms
- Must not be floated

Features and Advantages:

- Premium grade timber
- Can be sanded and re-finished
- 100% natural solid wood
- Ensures excellent thermal and acoustic isolation
- Floor can be laid in most residential areas (except those of high humidity)
- Elka complimentary accessory products available – underlay, adhesives, finishing profiles & maintenance products. View these at www.elkaflooring.com

See www.elkaflooring.com for warranty information