



## Protect & Maintain

PAGE 1/5

Validation date: 13/04/2006

### SAFETY DATA SHEET

#### 1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- Identification of the substance or preparation: ELKA WOOD FLOOR OIL SPECIAL MAINTENANCE

##### **Company/undertaking identification:**

- Registered company name: Spectrim Distribution
- Address: Unit 4, The Furrows, Barton Dock Rd Trafford Park Manchester M32 0SZ
- Telephone: 028 30 250477 Fax: 028 30 250223.

**Emergency telephone: Blanchon 00.33.1.45.42.59.59.**

#### 2 - COMPOSITION/INFORMATION ON INGREDIENTS

- Full text of risk phrases appearing in section 2: **see section 16.**
- Hazardous substances present on their own: (present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)
- This preparation contains no hazardous substance in this category.

##### **Other substances representing a hazard:**

CAS	EC	Name	Symb.	R:	%
64742-48-9	265-150-3	NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	Xn	65 10 66	50 <= x % < 100

- Substances present at a concentration below the minimum danger threshold:
- No known substance in this category present.
- Other substances with occupational exposure limits:
- No known substance in this category present.

##### **Other components:**

CAS	EC	Name	Symb.	R:	%
64742-48-9	265-150-3	NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	Xn	65 66	0 <= x % < 2.5

##### **May produce an allergic reaction:**

CAS	EC	Name	Symb.	R:	%
96-29-7	202-496-6	2-OXY-BUTANON	Xn	40.C3 41 43 21	0 <= x % < 2.5
68409-81-4	270-066-5	C6-19 FATTY-ACID, COBALT'S SALT (2+)	Xn	38 43 22	0 <= x % < 2.5

#### 3 - IDENTIFICATION OF HAZARDS

- **This product is classed:** Flammable.
- This preparation presents an aspiration hazard because of their low viscosity associated with a petroleum by-product.
- May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.

#### 4 - FIRST AID MEASURES

- As a general rule, in case of doubt or if symptoms persist, always call a doctor.
- **NEVER** induce swallowing in an unconscious person.
- ***In the event of exposure by inhalation:*** If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.
- ***In the event of splashes or contact with eyes:*** Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
- Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.
- ***In the event of splashes or contact with skin:*** Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
- DO NOT use solvents or thinners.
- ***In the event of swallowing:*** if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a Doctor. If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

#### 5 - FIRE-FIGHTING MEASURES

- Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.
- ***Suitable extinguishing media:*** Carbon dioxide, chemical powders, foams, and other extinguishing gases.
- In the event of fire, use specifically suitable extinguishing agents. Never use water.
- ***Extinguishing media which must not be used for safety reasons:*** Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.
- A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
- Do not breathe in smoke.
- Prevent the effluent of fire-fighting measures from entering drains or waterways.
- ***Special protective equipment for fire-fighters:*** Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

#### 6 - ACCIDENTAL RELEASE MEASURES

- ***Personal precautions:*** On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises.
- Avoid inhaling the vapors.
- Consult the safety measures listed under headings **7 and 8**.
- ***Environmental precautions:*** Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.
- Prevent any material from entering drains or waterways. Use drums to dispose of waste recovered in accordance with applicable regulations (**see heading 13**).
- ***If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures***
- ***Methods for cleaning up:*** Clean preferably with a detergent, do not use solvents.

#### 7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

- ***Handling:*** Handle in well-ventilated areas.
- The vapours are denser than air. They can spread along the ground and form explosive mixtures with air.
- Prevent the formation of flammable or explosive concentrations in air and avoid vapour concentrations higher than the occupational exposure limits.
- Never suck up this product.
- ***Fire prevention:*** Prevent the accumulation of electrostatic charges with connections to earth. The preparation may become electro-statically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.

- Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment
- Keep packages tightly closed and away from sources of heat, sparks and naked flames.
- Do not use tools which may produce sparks. Do not smoke.
- Prevent access by unauthorised personnel.
- **Recommended equipment and procedures:** For personal safety, **see §8.**
- Observe precautions stated on label and also industrial safety regulations.
- Packages which have been opened must be reclosed carefully and stored in an upright position.
- Avoid inhaling vapours.
- **Prohibited equipment and procedures:** Smoking, eating and drinking are prohibited in premises where the preparation is used.
- Never open the packages under pressure

**Storage:**

- Keep the container tightly closed in a dry place.
- Keep away from all sources of ignition - do not smoke.
- Keep well away from all sources of ignition, heat and direct sunlight
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Use personal protection equipment as per Directive 89/686/EEC.
- **Technical measures:** Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
- If this ventilation is insufficient to maintain the concentration of solvent vapours below the exposure limits, wear breathing apparatus
- **Respiratory protection:** Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.
- **Anti-gas filters:** - A1,A2,A3 (brown)
- **Hand protection:** Protective creams may be used for exposed skin, but they should not be applied after contact with the product.
- In the event of prolonged or repeated contact with the hands, use appropriate gloves.
- **Type of gloves recommended:** - Nitrile
- **Eye and face protection:** Use eye protectors designed to protect against liquid splashes
- **Skin protection:** For further information, **see § 11 of S.D.S.** - Toxicological information.

**9 - PHYSICAL AND CHEMICAL PROPERTIES**

General information:

- **Physical state:** fluid liquid
- Important health, safety and environmental information:
- **PH of the substance or preparation:** not relevant. The pH is impossible to measure or its value is not relevant.
- **Boiling point/boiling range:** 145 °C.
- **Flash point interval:** 23°C. < Flash point: <= 55°C.
  
- **Vapour pressure:** Below 110 kPa (1.10 bar).
- **Density:** < 1
- **Water solubility:** Insoluble.

Other information:

- **Melting point/melting range:** -20 °C.
- **Self-ignition temperature:** 200 °C.
- **Decomposition point/decomposition range:** not relevant.
- **V.O.C. :** 660 g/l.

**10 - STABILITY AND REACTIVITY**

- When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

**11 - TOXICOLOGICAL INFORMATION**

- No data is available regarding the preparation itself.
- Exposure to vapours from solvents contained in the preparation beyond the exposure limits stated may produce effects
- harmful to health, such as: Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.
- Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.
- Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic
- Dermatitis on contact and absorption through the epidermis.
- Splashes in the eyes may cause irritation and reversible damage

**12 - ECOLOGICAL INFORMATION**

- No ecological data on the product itself is available.
- The product must not be allowed to run into drains or waterways.

**13 - DISPOSAL CONSIDERATIONS**

- Do not pour into drains or waterways.

## Waste:

- Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.
- Do not contaminate the ground or water with waste; do not dispose of waste into the environment. Soiled packaging:
- Empty the container completely. Keep label(s) on container and give to a certified disposal contractor.

**14 - TRANSPORT INFORMATION**

- Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2005 - IMDG 2004 - ICAO/IATA 2005).
- UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	
	3	F1	III	3	30	LQ7	163-650-640E	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.		
	3	-	III	5 L	F-E,S-E	163 223 944 955		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note
	3	-	III	309	60 L	310	220 L	A3 A72
	3	-	III	Y309	10 L	-	-	-

**15 - STATUTORY INFORMATION**

- This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations
- In addition directive 2004/73/EC with the 29°adapt ation of directive 67/548/EEC (Hazardous substances) have been taken into account.

## Preparation classification:

- Harmful. Flammable.

## Contains:

- Contains 2-OXY-BUTANON. May produce an allergic reaction.

- Contains C6-19 FATTY-ACID, COBALT'S SALT (2+). May produce an allergic reaction.
- NAPHTHA (PETROLEUM), HYDROTREATED HEAVY
- Particular hazards associated with the preparation and safety recommendations:
- R 10 Flammable.
- R 65 Harmful. May cause lung damage if swallowed.
- R 66 Repeated exposure may cause skin dryness or cracking.
- S 2 Keep out of reach of children.
- S 46 If swallowed, seek medical advice immediately and show this container or label.
- S 23 Do not breathe vapour.
- S 24 Avoid contact with skin.
- S 51 Use only in well ventilated areas.
- S 62 If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label

**Particular provisions:**

- Child-resistant fastenings (Annex IV A2- 1999/45/EC)
- Tactile warning of danger.

**16 - OTHER INFORMATION**

- Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.
- The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.
- It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.
- The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties
- Full text of risk phrases appearing in section 2:
- R 10 Flammable.
- R 21 Harmful in contact with skin.
- R 22 Harmful if swallowed.
- R 38 Irritating to skin.
- R 40.C3 Limited evidence of a carcinogenic effect.
- R 41 Risk of serious damage to eyes.
- R 43 May cause sensitization by skin contact.
- R 65 Harmful. May cause lung damage if swallowed.
- R 66 Repeated exposure may cause skin dryness or cracking.

For further information on this product visit [www.elkaflooring.com](http://www.elkaflooring.com)

Elka is brand registered & imported by Spectrim Distribution Ltd, details available at [www.spectrim.co.uk](http://www.spectrim.co.uk)