

# 7mm laminate flooring



# ELKA



## elka clic

Produced under licence of Unilin  
EU patent 0 843 763 B1  
U.S. patent nr. 6,006,486



### Specification

- 2.201m<sup>2</sup> packs 1287x190x7mm

### Key Features

- Fully integrated 'Elka clic' installation system
- High definition surface structures
- Latest styles combined with quality German technology
- Choice of modern finishes and individualistic designs
- Handy 1.938m<sup>2</sup> packs 1380x156x8mm
- 15yr domestic warranty.

### Advantages

- Super fast and proven installation system
- Flexible fitting options - you can start anywhere within the room
- Hygienic allergy reducing floor
- Can be used in conjunction with noise reducing underlay
- Suitable for use with under floor heating.

### Range 'E' = Embossed surface

- Country Oak 'E'
- Dark Smoked Ash 'E'
- Enhanced Beech
- Enhanced Walnut
- American Birch
- Rustic Oak
- Warn Chestnut
- Mat Oiled Oak



### TECHNICAL SPECIFICATION

COUNTRY OF ORIGIN: Germany.

STANDARD: EN13329

SUITABILITY: All Domestic Locations  
Light Commercial  
Class: 31  
Rated: AC3

WARRANTY: 15 years (domestic)

INSTALLATION: Uniclic Locking System.  
(No glue required)

BASE BOARD: 7mm HDF core  
Moisture resistant

MANUFACTURING TECHNIQUE: Direct pressed laminate.

### INDUSTRY TESTS ON ELKA 7mm LAMINATE FLOORING

BS 476,7	FIRE CATEGORY	EN 438-2,16 LIGHT FASTNESS
ISO 4586-2	WEAR RESISTANCE	EN 438-2,14 SCRATCH RESISTANCE
ISO 717-2	ACOUSTICS	EN 438-2,12 IMPACT RESISTANCE
E1 STANDARD	FORMALDHYDE	EN 438-2,15 STAINS & CLEANING